Attorney Docket No. DUVA-001

APPLICATION

FOR UNITED STATES LETTERS PATENT

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT I, **Richard J. Duval**, a citizen of Canada, have invented a new and useful optical stitch regulator system of which the following is a specification:

Optical Stitch Regulator System

CROSS REFERENCE TO RELATED APPLICATIONS

Not applicable to this application.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

Not applicable to this application.

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates generally to sewing machine stitch regulators and more specifically it relates to an optical stitch regulator system for efficiently regulating the stitch length and stitch frequency of a sewing machine.

Description of the Related Art

Conventional stitch regulators for sewing machines have been in use for years. Conventional stitch regulators utilize wheel based encoders that are attached to the frame of the sewing machine.

One of the problems with conventional stitch regulators is that they require multiple wheel based encoders – one for each axis of movement. A further problem with conventional stitch regulators is that they must be utilized upon a straight and smooth surface. A further problem with conventional stitch regulators is that they are dependent upon equipment installed upon the XY carriages to provide the motion feedback of the piece being sewn. Another problem with conventional stitch regulators is that they require external wiring and encoders which can be damaged. Conventional stitch regulators utilize mechanical feedback devices that are dependent upon the XY carriages of the sewing machine and that can be damaged during operation of the sewing machine.

In these respects, the optical stitch regulator system according to the present invention substantially departs from the conventional concepts and designs of the prior art, and in so doing provides an apparatus primarily developed for the purpose of efficiently regulating the stitch length and stitch frequency of a sewing machine.

BRIEF SUMMARY OF THE INVENTION

In view of the foregoing disadvantages inherent in the known types of stitch regulators now present in the prior art, the present invention provides a new optical stitch regulator system construction wherein the same can be utilized for efficiently regulating the stitch length and stitch frequency of a sewing machine.

The general purpose of the present invention, which will be described subsequently in greater detail, is to provide a new optical stitch regulator system that has many of the advantages of the stitch regulators mentioned heretofore and many novel features that result in a new optical stitch regulator system which is not anticipated, rendered obvious, suggested, or even implied by any of the prior art stitch regulators, either alone or in any combination thereof.

To attain this, the present invention generally comprises an optical sensor within or external of the sewing platform of a sewing machine for sensing the motion of the fabric being sewn. The motion data is communicated to a control unit which communicates with the sewing machine for controlling the stitch length and frequency.

There has thus been outlined, rather broadly, the more important features of the invention in order that the detailed description thereof may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the invention that will be described hereinafter and that will form the subject matter of the claims appended hereto.

In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the

following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein are for the purpose of the description and should not be regarded as limiting.

A primary object of the present invention is to provide an optical stitch regulator system that will overcome the shortcomings of the prior art devices.

A second object is to provide an optical stitch regulator system for efficiently regulating the stitch length and stitch frequency of a sewing machine.

Another object is to provide an optical stitch regulator system that does not require external or mechanical feedback devices.

An additional object is to provide an optical stitch regulator system that can be self-contained within a sewing machine.

A further object is to provide an optical stitch regulator system that may be utilized within new or existing sewing machines.

Another object is to provide an optical stitch regulator system that provides motion feedback of the fabric being sewn independent of the carriage assemblies.

Other objects and advantages of the present invention will become obvious to the reader and it is intended that these objects and advantages are within the scope of the present invention.

To the accomplishment of the above and related objects, this invention may be embodied in the form illustrated in the accompanying drawings, attention being called

to the fact, however, that the drawings are illustrative only, and that changes may be made in the specific construction illustrated and described within the scope of the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

Various other objects, features and attendant advantages of the present invention will become fully appreciated as the same becomes better understood when considered in conjunction with the accompanying drawings, in which like reference characters designate the same or similar parts throughout the several views, and wherein:

FIG. 1 is an upper perspective view of the present invention.

FIG. 2 is a magnified upper perspective view of the present invention.

FIG. 3 is a side view of the present invention.

FIG. 4 is an upper perspective view of the present invention sewing a piece of fabric.

FIG. 5 is a side cutaway view of the present invention sewing a piece of fabric.

FIG. 6 is an upper perspective view of an alternative embodiment illustrating an exemplary aftermarket attachment.

FIG. 7 is a side view of a second alternative embodiment illustrating an exemplary aftermarket attachment.

FIG. 8 is a block diagram of the present invention.

FIG. 9 illustrates a third alternative embodiment wherein the optical sensors are positioned around the needle for determining when a piece of fabric is entering the sewing area of the needle.

DETAILED DESCRIPTION OF THE INVENTION

A. Overview

Turning now descriptively to the drawings, in which similar reference characters denote similar elements throughout the several views, FIGS. 1 through 9 illustrate an optical stitch regulator system **10**, which comprises an optical sensor **30** within or external of the sewing platform **24** of a sewing machine **20** for sensing the motion of the fabric **12** being sewn. The motion data is communicated to a control unit **40** which communicates with the sewing machine **20** for controlling the stitch length and frequency.

B. Sewing Machine

The sewing machine **20** may be comprised of any conventional sewing machine **20** (e.g. personal, commercial, industrial). The sewing machine **20** may have various structures and functionality other than shown in Figures 1 through 7 of the drawings. For example, the sewing machine **20** may be comprised of a long arm quilting machine wherein the needle **22** is moved relative to the fabric **12** by utilizing carriages to move the needle **22** relative to a fabric **12**.

The sewing machine **20** may have its own internal control unit **40** for controlling the stitch length based upon the movement feedback from the optical sensor **30**. If the sewing machine **20** does not have an internal control unit **40**, then an external control unit **40** is in communication with the sewing machine **20**. The control unit **40** controls the motor speed of the sewing machine **20** based upon the movement feedback (e.g. direction, velocity) from the optical sensor **30** so as to maintain a consistent and desired stitching pattern of the fabric **12**. For example, if the optical sensor **30** provides movement feedback that the fabric **12** entry velocity has increased, then the sewing machine **20** will increase the motor speed accordingly.

C. Optical Sensor

One or more optical sensors **30** are preferably attached to the sewing machine **20** or a sewing machine carriage for measuring a movement (e.g. direction, velocity) of a piece of fabric **12** being sewn. It can be appreciated that the optical sensors **30** may be attached to a structure external of the sewing machine **20** or the sewing machine carriage. The optical sensor **30** is in communication with the sewing machine **20** regarding the movement of the fabric **12** so that the sewing machine **20** may adjust the motor accordingly to provide a desired stitching pattern.

The optical sensor **30** is preferably positioned within a sewing platform **24** of the sewing machine **20** as shown in Figures 1 through 6 of the drawings. The optical sensor **30** is preferably directed substantially upwardly towards the lower surface of the fabric **12** being sewn as best illustrated in Figures 3 and 5 of the drawings. The optical sensor **30** preferably extends a finite distance above the sewing platform **24** of the sewing machine **20** to maintain constant contact with the fabric **12** as best illustrated in Figure 5 of the drawings.

The optical sensor **30** preferably has a curved outer lens as best shown in Figures 3 and 5 of the drawings. Alternatively, the optical sensor **30** may also have a flat outer lens as can also be appreciated.

The optical sensor **30** is preferably positioned near the needle **22** of the sewing machine **20** as shown in Figures 1, 2 and 5 of the drawings. With the optical sensor **30** positioned in front of the needle **22**, the optical sensor **30** is capable of measuring the movement of the fabric **12** entering the needle **22**.

The optical sensor **30** is capable of measuring at least one direction of the movement (e.g. an X-axis, Y-axis). The optical sensor **30** is also preferably capable of measuring a velocity of the movement.

The optical sensor **30** is preferably comprised of a combination light source and a light receiver similar in technology to that commonly utilized within an optical computer mouse. The light receiver detects light reflected by a piece of fabric **12** and based upon this information is able to calculate the relative movement of the fabric **12** with respect to the sewing machine **20**. The light source may be a light emitting diode or other commonly utilized light source. U.S. Patent No. 6,501,460 teaches a "light-receiving unit for optical mouse" which is hereby incorporated by reference for teaching an exemplary light source that may be utilized within the present invention.

Figure 9 illustrates utilizing more than one optical sensor **30** positioned about various sides of the needle **22** for determining when a piece of fabric **12** enters the sewing area of the needle **22**. By positioning the optical sensors **30** about four or more sides of the sewing area, it can be determined if a piece of fabric **12** is entering the sewing area from various angles and approaches. It can be appreciated the plurality of optical sensors **30** shown in Figure 9 may also extend from above the fabric **12** or from a sewing machine carriage.

D. Control Unit

The control unit **40** is in communication between the optical sensor **30** and the sewing machine **20** as shown in Figure 8 of the drawings. The control unit **40** may be internal or external (Figures 6 and 7) of the sewing machine **20**. The control unit **40** may also be integrated within the optical sensor **30**.

The control unit **40** is preferably comprised of a motion interpretation module that transmits movement information to the sewing machine **20** and thereby controls the

speed of the sewing machine **20** based upon the movement of the fabric **12**. The motor control module within the sewing machine **20** receives the movement data from the control unit **40** (or directly from the optical sensor **30**) and then controls the motor of the sewing machine **20** accordingly. The control unit **40** may include various other control features such as control knobs for controlling the stitching pattern and the like.

E. Support Member

Alternatively, the optical sensor **30** is directed downwardly as shown in Figure 7 of the drawings. A support member **50** is attached to a portion of the sewing machine **20** and supports the optical sensor **30** in a downward manner. It is preferable that the optical sensor **30** be positioned relatively close to the upper surface of the fabric **12** being sewn. An attachment member **52** (e.g. band) or other attachment means attaches the support member **50** to the upper portion of the sewing machine **20** as further shown in Figure 7 of the drawings.

F. Operation of Invention

In use, the user positions the fabric **12** to be sewn upon the sewing platform **24** of the sewing machine **20**. The sewing machine **20** is preferably preset to a desired stitching pattern. The user then causes the fabric **12** to move relative to the needle **22** of the sewing machine **20** and the sewing machine **20** begins to sew the fabric **12** by causing the needle **22** to reciprocate in a desired frequency.

The optical sensor **30** senses the movement of the fabric **12** with respect to the needle **22** and then provides this movement data to the control unit **40**. The control unit **40** then communicates with the sewing machine **20** and the motor of the sewing machine **20** is adjusted accordingly. For example, if the fabric **12** speed is increased then the sewing machine **20** will increase the motor speed to increase the frequency of the needle **22** movement. If the fabric **12** speed is decreased then the sewing machine **20** will decrease the motor speed to decrease the frequency of the needle **22** movement.

This allows the sewing machine **20** to provide a consistent stitching pattern regardless of the movement of the fabric **12**.

What has been described and illustrated herein is a preferred embodiment of the invention along with some of its variations. The terms, descriptions and figures used herein are set forth by way of illustration only and are not meant as limitations. Those skilled in the art will recognize that many variations are possible within the spirit and scope of the invention, which is intended to be defined by the following claims (and their equivalents) in which all terms are meant in their broadest reasonable sense unless otherwise indicated. Any headings utilized within the description are for convenience only and have no legal or limiting effect.